TEKIN RS SETUP SHEET
RS + RS PRO

DRIVER: Steve Salvas
VEHICLE: 1s-17.5 carpet oval 1/10
TRACK: 145-170' (Snowbird Nats)
SURFACE: Ozite Carpet
TRACTION: LOW ☐ MED ☑ HIGH ☑

MOTOR: SS / Ballistic
ENDBELL TIMING: Full CCW / (+)
ROTOR: 12.25mm
GEARING: 4.35" rollout
BATTERY: SMC 1s 6000mAh 28C

ESC SETTINGS:

ESC Firmware Version: 212
HotWire Software Version: 5.7.3

BOOST	START RPM	END RPM	TURBO DELAY	TURBO	TURBO RAMP
50	917	6493	n/a	0	n/a

MOTOR TYPE: BL-FW
VOLTAGE CUTOFF: 1S
DRIVE MODE: Sensored
MOTOR DIRECTION: Normal
THROTTLE PROFILE: 3
CURRENT LIMITER: Off

DRAG BRAKE: Off
MINIMUM BRAKE: 10
MINIMUM THROTTLE: 10
BRAKE STRENGTH: 100
REVERSE SPEED: Off
NEUTRAL WIDTH: Min
PUSH CONTROL: Off

NOTES:

Timing Profile : C1 or C2