TEKIN RS SETUP SHEET
RS + RS PRO

DRIVER:	Steve Salvas
VEHICLE:	1s-7.5 carpet oval 1/10
TRACK:	145-170' (Snowbird Nats)
SURFACE:	Ozite Carpet
TRACTION:	LOW ☐ MED ✔ HIGH ✔

MOTOR:	Tekin Redline
ENDBELL TIMING:	14 degrees
ROTOR:	12.50mm
GEARING:	2.85" rollout
BATTERY:	SMC 1s 6000mAh 28C

ESC SETTINGS:

ESC Firmware Version: 212

HotWire Software Version: 5.7.3

BOOST	START RPM	END RPM	TURBO DELAY	TURBO	TURBO RAMP
44	864	11444	n/a	0	n/a

MOTOR TYPE:	BL-FW
VOLTAGE CUTOFF:	1S
DRIVE MODE:	Sensored
MOTOR DIRECTION:	Normal
THROTTLE PROFILE:	3
CURRENT LIMITER:	Off

DRAG BRAKE:	Off
MINIMUM BRAKE:	10
MINIMUM THROTTLE:	10
BRAKE STRENGTH:	100
REVERSE SPEED:	Off
NEUTRAL WIDTH:	Min
PUSH CONTROL:	Off

NOTES:

Timing Profile : C1 or C2