TEKIN

RS SETUP SHEET
RS + RS PRO

DRIVER:	Steve Salvas
VEHICLE:	1/10 DODC 13.5
TRACK:	145'
SURFACE:	Dirt Oval (Hard Packed Clay)
TRACTION:	LOW ☐ MED ☑ HIGH ☑

MOTOR:	DODC 13.5
ENDBELL TIMING:	See Notes
ROTOR:	DODC
GEARING:	2.05" Rollout (145')
BATTERY:	DODC 3200mAh

ESC SETTINGS:

ESC Firmware Version: Vegas 212

HotWire Software Version: 5.7.1

BOOST	START RPM	END RPM	TURBO DELAY	TURBO	TURBO RAMP
47	2883	12602	n/a	0	n/a

MOTOR TYPE:	DODC 13.5
VOLTAGE CUTOFF:	2s
DRIVE MODE:	Sensored
MOTOR DIRECTION:	Normal
THROTTLE PROFILE:	2
CURRENT LIMITER:	Off

DRAG BRAKE:	Off
MINIMUM BRAKE:	0
MINIMUM THROTTLE:	0
BRAKE STRENGTH:	100
REVERSE SPEED:	Off
NEUTRAL WIDTH:	Min
PUSH CONTROL:	100

NOTES:

Motor Timing : Almost full counterclocwise ... timing notch against soldering tab.